

Manufacturer's Safety and Quality Assurance Certificate

This certificate relates only to the individual product detailed below.
Visit www.airquee.com for more information. **This is the test certificate for your new inflatable. Please keep this in a safe place. This is valid for one year from the date below.**



Product: 1.4m x 2.6m Kick n' Stick

Tag No: 66213

Valid From: 07-04-2025

Serial/Certificate no: P65951 **Code:** AO0002

Weight: Unit: 21kg Total: 27kg

| Structure | Pass | Fail | N/A |
|-------------------------|------|------|-----|
| Trough Depth | X | | |
| Seam Security | X | | |
| Stitching | X | | |
| Walls & Towers | X | | |
| Can Walls Contain Users | | | X |
| Fall Off Height (FOH) | | | X |
| Grounding | X | | |
| Stability | X | | |
| Entrapment | | | X |
| Sharp Angles | X | | |
| Zip(s) | X | | |
| Windows | | | X |
| Netting | | | X |
| Clamber Netting | | | X |
| Air Loss Points | X | | |
| Markings | X | | |
| Artwork | X | | |
| Identification | X | | |

| Materials | Pass | Fail | N/A |
|-------------------------------|------|------|-----|
| Fabric Material and Condition | X | | |
| Thread Condition | X | | |
| Material Fire Retardancy | X | | |
| De-lamination of PVC | X | | |

| Anchorage | Pass | Fail | N/A |
|------------------------|------|------|-----|
| Total No of Anchors | X | | |
| Anchor Point Integrity | X | | |
| Anchor Point Location | X | | |
| Anchor Type | X | | |
| Anchor Accessories | X | | |
| Ropes | | | X |

| Blower | Pass | Fail | N/A |
|---------------------------|------|------|-----|
| Kilopascal (kPa) | X | | |
| Size & Type | X | | |
| Inlet & Outlet Mesh | X | | |
| Cable & Plug | X | | |
| Casing & Impeller | X | | |
| Pat Test | | | X |
| Return Flap | X | | |
| Blower Tube(s) / Valve(s) | X | | |

| Enterances, Exits & Evacuation | Pass | Fail | N/A |
|--------------------------------|------|------|-----|
| Deflation / Evacuation Time | | | X |
| Length of Step | | | X |

| Totally Enclosed Structures | Pass | Fail | N/A |
|-----------------------------|------|------|-----|
| Exits | | | X |
| Exit Markings | | | X |
| Lighting Supports | | | X |
| Emergency Lighting | | | X |
| Deflation Speed | | | X |
| User Area Pressure | | | X |

| Slides | Pass | Fail | N/A |
|-------------------------------|------|------|-----|
| Wall Height / Platform Height | | | X |
| Run-Out | | | X |
| Clamber Step | | | X |
| Slide Sheet | | | X |

| Notes |
|---|
| Indoor Use Only: No Label Location: rear side Length: 1.45m Width: 2.6m Height: 2.7m Zips: 1 pcs (exterior velcro flap + interior non return flap) Netting: N/A Roof : N/A Artwork : printed + laq UV |

| Notes |
|--|
| Material : gloss 450g pvc + 520 g printable material |

| Notes |
|--|
| Calculated Anchors: 6 Anchor points: 6 pcs PVC & metal triangle Bottom Supplied anchor accessories: 6 pcs / 400 mm* 18 mm metal pegs |

| Notes |
|--|
| kPa: 1.35 Blower minimum pressure: 1.00 Blower power: 1 pcs 1.5HP Blower tube length: 1.23 m Position: 1 pcs rear side |

| Notes |
|------------------------------------|
| Enclosed Unit: Yes Step Length: |

| Notes |
|-------|
| |

| Notes |
|--|
| Platform roof fitted: No Slide sheet: N/A |

| Users |
|--|
| Max User Height: 1.8 Max Users upto 1m: 1 Max Users upto 1.25m: 1 Max Users upto 1.5m: 1 Max Users over 1.8: 1 |

SIGNED BY: Demeter Attila
PIPA ANNUAL INFLATABLE INSPECTOR

